			·			
TRANSMITTAL FORM			Application No.	10/58	10/586,800	
		Filing Date	July 1	July 13, 2006		
(to be used for all correspondence after initial filing)		First Named Inventor	Yong	xiang Han		
		Art Unit	2616	•		
		Examiner Name				
Total Number of Pa	ges in This Submission	n	Attorney Docket Numbe	42P2	1623	
	ENCLO	SURES (chec	k all that apply)			
Fee Transmittal	Form	Drawing(s)			After Allowance Communication to TC	
Fee Attac	hed	Licensing-related Papers			Appeal Communication to Board of Appeals and Interferences	
Amendment / Reply		Petition			Appeal Communication to TC (Appeal Notice, Brief, Reply Brief)	
After Final Affidavits/declaration(s)		Petition to Convert a Provisional Application			Proprietary Information	
Extension of Time Request		Power of Attorney, Revocation Change of Correspondence Address			Status Letter	
Express Abandonment Request		Terminal Disclaimer		×	Other Enclosure(s) (please identify below):	
Information Disclosure Statement		Request fo	r Refund	-1	Return postcard	
PTO/SB/0	08	CD, Number of CD(s)				
Certified Copy of Priority Document(s)		Lands	cape Table on CD			
Response to Missing Parts/ Incomplete Application Basic Filing Fee		Remarks				
Declaration/POA  Response to Missing Parts under 37 CFR 1.52 or 1.53						
	SIGNATURI	I E OF APPLICAI	NT, ATTORNEY, OR A	GENT		
Firm	Paul A. Mendor	nsa, Reg. No. 4	42,879			
<i>or</i> Individual name		_	TAYLOR & ZAFN	IAN L	LP	
Signature						
Date January 25, 2007						
CERTIFICATE OF MAILING/TRANSMISSION						
I hereby certify that this correspondence is being deposited with the United States Postal Service on the date shown below with sufficient postage as first class mail in an envelope addressed to: Mail Stop PCT, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.						
Typed or printed name Katherine Jennings						
Signature ( ) Signature Date January 25, 2007				January 25, 2007		

Based on PTO/SB/21 (09-04) as modified by Blakely, Solokoff, Taylor & Zafman (not) 10/12/2006. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1459

#### Complete if Known **FEE TRANSMITTAL** Application Number 10/586,800 for FY 2006 Filing Date July 13, 2006 Patent fees are subject to annual revision. First Named Inventor Yongxiang Han **Examiner Name** Applicant claims small entity status. See 37 CFR 1.27. Art Unit 2616 TOTAL AMOUNT OF PAYMENT Attorney Docket No. 42P21623 METHOD OF PAYMENT (check all that apply) ☐ Check ☐ Credit card ☐ Money Order ☒ None Other (please identify): Deposit Account Deposit Account Number: 02-2666 Deposit Account Name: Blakely, Sokoloff, Taylor & Zafman LLP For the above-identified deposit account, the Director is hereby authorized to: (check all that apply) Charge fee(s) indicated below, except for the filing fee ☐ Charge fee(s) indicated below Charge any additional fee(s) or underpayment of fee(s) Credit any overpayments under 37 CFR §§ 1.16, 1.17, 1.18 and 1.20. **FEE CALCULATION** Large Entity Small Entity Fee Fee Fee Fee Fee Description Fee Paid Code (\$) Code (\$) 1051 130 2051 65 Surcharge - late filing fee or oath 1052 50 2052 25 Surcharge - late provisional filing fee or cover sheet. 2053 2053 130 130 Non-English specification 1251 120 2251 60 Extension for reply within first month 1252 450 2252 225 Extension for reply within second month 1253 1,020 2253 510 Extension for reply within third month 1254 1,590 2254 795 Extension for reply within fourth month 1255 2,160 2255 1,080 Extension for reply within fifth month 1401 500 2401 250 Notice of Appeal 1402 500 2402 <sup>250</sup> Filing a brief in support of an appeal 1403 1.000 2403 500 Request for oral hearing 1451 1.510 2451 1,510 Petition to institute a public use proceeding 1460 130 2460 130 Petitions to the Commissioner 1807 50 1807 <sup>50</sup> Processing fee under 37 CFR 1.17(q) 1806 180 1806 180 Submission of Information Disclosure Stmt 1809 790 1809 395 Filing a submission after final rejection (37 CFR § 1.129(a)) 1810 790 2810 395 For each additional invention to be examined (37 CFR § 1.129(b)) Other fee (specify) SUBTOTAL (2) SUBMITTED BY Complete (if applicable) Registration No. Name (Print/Type) Paul A. Mendonsa Telephone (503) 439-8778 42,879 (Attorney/Agent) 01/25/07 Signature Date

中华人民共和国国家知识产权局 STATE INTELLECTUAL PROPERTY OFFICE OF THE PEOPLE'S REPUBLIC OF CHINA



# 证明

### **CERTIFICATE**

本证明之附件是向中国专利局作为受理局提交的下列国际申请副本<sup>'</sup>
HIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY OF THE BELOW
IDENTIFIED INTERNATIONAL APPLICATION THAT WAS FILED WITH THE
CHINESE PATENT OFFICE AS RECEIVING OFFICE

际申请号:

PCT/CN2005/001594

RNATIONAL APPLICATION NUMBER

申请日:

28. SEP 2005 (28. 09. 2005)

NATILNAL FILING DATE

月名称:

UPDATING ENTRIES CACHED BY A NETWORK PROCESSOR

F INVENTION



CERTIFIED COPY OF PRIORITY DOCUMENT

中华人民共和国国家知识产权局局长
COMMISSIONER OF THE STATE INTELLECTUAL PROPERTY
OFFECE OF THE PEOPLE'S REPUBLIC OF CHINA

包为黄

二零零七年一月五日

## **PCT**

### REQUEST

### HOME

COPY

The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty.

For receiving Office use only

PCT/CN 2005 / 0 0 1 5 9 4

28 · SEP 2005'(2 8 · 0 9 · 2 0 0 5)

International Filing Date

一〇/CN 中华人民共和国国家知识产权局me of receiving Office Smill 中tor matinaman AlphrinderHin

Applicant's or agent's file reference (if desired) (12 characters maximum) FPEL05150044

	<del> </del>			
BOX NO. I TITLE OF INVENTION UPDATING ENTRIES CACHED BY A NETWORK PROCESSOR				
Box No. II APPLICANT				
Name and address: (Family name followed by given name; for a legal entity, full official designation.  The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)	Telephone No.			
INTEL CORPORATION	Facsimile No.			
2200 Mission College Blvd.	Talaniatas No.			
Santa Clara, California 95052 United States of America	Teleprinter No.			
United States of America	Applicant's registration No. with the Office			
State (that is, country) of nationality:  US  State (that is, country)  US	I of residence:			
This person is applicant for the purposes of:  all designated States except the United States of America	the United States of America only the States indicated in the Supplemental Box			
Box No. III FURTHER APPLICANT(S) AND/OR (FURTHER) INVENTOR(S)	·			
Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)  HAN, Yongxiang 6th Floor, North Office Tower, #06-01  Beijing Kerry Centre 1, Guanghua Road  Chaoyang District, Beijing 100020  P. R. of China	This person is:  applicant only  applicant and inventor  inventor only (If this check-box is marked, do not fill in below.)  Applicant's registration No. with the Office			
State (that is, country) of nationality: US  State (that is, country) US	of residence:			
This person is applicant for the purposes of:  all designated states except the United States of America	the United States of America only the States indicated in the Supplemental Box			
Further applicants and/or (further) inventors are indicated on a continuation sheet.				
Box No. IV AGENT OR COMMON REPRESENTATIVE; OR ADDRESS FOR	CORRESPONDENCE			
The person identified below is hereby/has been appointed to act on behalf of the applicant(s) before the competent International Authorities as:	agent common representative			
Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country.)	Telephone No. (852)28284688			
China Patent Agent (H.K.) Ltd.	Facsimile No.			
22/F, Great Eagle Centre	(852)28271018			
23 Harbour Road, Wanchai Hong Kong Special Administrative Region	Teleprinter No.			
The People's Republic of China	A single control of the control of t			
	Agent's registration No. with the Office			
Address for correspondence: Mark this check-box where no agent or common representative is/has been appointed and the space above is used instead to indicate a special address to which correspondence should be sent.				

Sheet No. ...2...

Continuation of Box No. III FURTHER APPLICANT(S) AND/OR (FURTHER) INVENTOR(S)					
If none of the following sub-boxes is used, this sheet should not be included in the request.					
Name and address: (Family name followed by given name; for a legal entity The address must include postal code and name of country. The country of the Box is the applicant's State (that is, country) of residence if no State of residence ZHANG, Yu 6th Floor, North Office Tower, #06-01 Beijing Kerry Centre 1, Guanghua Road Chaoyang District, Beijing 100020 P. R. of China  State (that is, country) of nationality:	address indicated in this				
This person is applicant all designated for the purposes of:  all designated the United States	States except the United States the States indicates of America only the Supplementa				
Name and address: (Family name followed by given name; for a legal entity. The address must include postal code and name of country. The country of the Box is the applicant's State (that is, country) of residence if no State of residence YU, Zhihong 6th Floor, North Office Tower, #06-01 Beijing Kerry Centre 1, Guanghua Road Chaoyang District, Beijing 100020 P. R. of China	address indicated in this	)			
State (that is, country) of nationality: CN	State (that is, country) of residence: CN				
This person is applicant all designated for the purposes of:	States except the United States of America only the States indicates of America only the Supplementation				
Name and address: (Family name followed by given name; for a legal entil The address must include postal code and name of country. The country of th Box is the applicant's State (that is, country) of residence if no State of residence	e address indicated in this	) .			
State (that is, country) of nationality:	State (that is, country) of residence:				
This person is applicant all designated all designated for the purposes of:	States except the United States the States indicates of America only the Supplementation	ted in d Box			
Name and address: (Family name followed by given name; for a legal enti The address must include postal code and name of country. The country of the Box is the applicant's State (that is, country) of residence if no State of residence.	e address indicated in this	) 			
State (that is, country) of nationality:	State (that is, country) of residence:				
This person is applicant all designated for the purposes of:	States except the United States the States indicates of America only the Supplement				
Further applicants and/or (further) inventors are indicated on another continuation sheet.					

Sheet No. ...3...

Box No. V DESIGNAT	Box No. V DESIGNATIONS				
	stitutes under Rule 4.9(a), the very kind of protection availa				
However,					
DE Germany is not de	esignated for any kind of nation	onal protection			
KR Republic of Korea	is not designated for any kir	nd of national protection			
RU Russian Federatio.	n is not designated for any k	ind of national protection	-		
the national law, of an earlie	be used to exclude (irrevocab r national application from w in these and certain other St	hich priority is claimed. S			
Box No. VI PRIORITY	CLAIM				
The priority of the following	earlier application(s) is hereb	y claimed:			
Filing date	Number	Where earlier application is:			
of earlier application (day/month/year)	of earlier application	national application: country or Member of WTO	regional application:* regional Office	international application: receiving Office	
item (1)					
item (2)					
item (3)					
Further priority claims a	are indicated in the Suppleme	ntal Box.			
	The receiving Office is requested to prepare and transmit to the International Bureau a certified copy of the earlier application(s) (only if the earlier application was filed with the Office which for the purposes of this international application is the receiving Office) identified above as:				
all items ite	em (1) item (2)	) item (3)	other, se	ee Supplemental Box	
* Where the earlier application	on is an ARIPO application, in ember of the World Trade Or	ndicate at least one country	y party to the Paris Conve	ention for the Protection of	
Box No. VII INTERNATIONAL SEARCHING AUTHORITY					
Choice of International Searching Authority (ISA) (if two or more International Searching Authorities are competent to carry out the international search, indicate the Authority chosen; the two-letter code may be used):					
ISA / CN					
Request to use results of earlier search; reference to that search (if an earlier search has been carried out by or requested from the International Searching Authority):					
Date (day/month/year)	Numb	er Coun	try (or regional Office)		
Box No. VIII DECLARATIONS					
The following declarations are contained in Boxes Nos. VIII (i) to (v) (mark the applicable  Number of check-boxes below and indicate in the right column the number of each type of declaration):  Number of declarations					
Box No. VIII (i) Declaration as to the identity of the inventor :					
Box No. VIII (ii)  Declaration as to the applicant's entitlement, as at the international filing date, to apply for and be granted a patent:					
Box No. VIII (iii) Declaration as to the applicant's entitlement, as at the international filing date, to claim the priority of the earlier application :					
Box No. VIII (iv)	Box No. VIII (iv)  Declaration of inventorship (only for the purposes of the designation of the United States of America)				
Box No. VIII (v) Declaration as to non-prejudicial disclosures or exceptions to lack of novelty :					

Sheet No. ...4

- A	
**	

Box No. IX CHECK LIST; LANGUAGE OF FILING					
This international application contains:  (a) in paper form, the following number of  This international application is accompanied by the following item(s) (mark the applicable check-boxes below and indicate in of items					
sheets:	right colum	: 1			
request (including declaration sheets) : 4	<ol> <li>fee calculation sheet</li> <li>original separate power of attorney</li> </ol>				
description (excluding		iginal general power of attorney	: 1		
sequence listing and/or tables related thereto) : 12		py of general power of attorney; reference number,	·		
claims : 7		any:	:		
abstract : 1	5. 🔲 sta	tement explaining lack of signature	:		
drawings 4 5 (4)	6. ☐ pri ite	iority document(s) identified in Box No. VI as m(s):	:		
Sub-total number of sheets: 2 [28] sequence listing	7. ☐ tra (la	inslation of international application into	:		
tables related thereto :  (for both, actual number of		parate indications concerning deposited microorganism other biological material	:		
sheets if filed in paper form, whether or not also filed in	9. 🔲 sed	quence listing in computer readable form idicate type and number of carriers)	·		
computer readable form; see (c) below)		copy submitted for the purposes of international search Rule 13 <i>ter</i> only (and not as part of the international app.	under		
Total number of sheets : 29 (28)	(ii) 🗆	(only where check-box (b)(i) or (c)(i) is marked in left column additional copies including, where applicable, the copy	mn)		
(b) ☐ only in computer readable form (Section 801(a)(i))	<b>-</b>	purposes of international search under Rule 13ter	;		
(i) ☐ sequence listing (ii) ☐ tables related thereto		together with relevant statement as to the identity of the copies with the sequence listing mentioned in left columns.	ın :		
(c) also in computer readable form (Section 801(a)(ii))		oles in computer readable form related to sequence listing adicate type and number of carriers)	3		
(i) sequence listing	(i) 🗆	copy submitted for the purposes of international search Section 802(b-quater) only (and not as part of the intern	under iational		
<ul><li>(ii) ☐ tables related thereto</li><li>Type and number of carriers (diskette,</li></ul>	(ii) $\square$	application)	:		
CD-ROM, CD-R or other) on which are contained the	(11)	(only where check-box (b)(ii) or (c)(ii) is marked in left col additional copies including, where applicable, the copy purposes of international search under Section 802(b-qu	for the		
sequence listing:	(iii) 🔲	together with relevant statement as to the identity of the			
tables related thereto:		copies with the tables mentioned in left column	;		
(additional copies to be indicated under items 9(ii) and/or 10(ii), in right column)	11. 🔟 oti	her (specify):	:		
Figure of the drawings which should accompany the abstract:		of filing of the al application:			
Box No. X SIGNATURE OF APPLICANT	Γ, AGENT C	OR COMMON REPRESENTATIVE  procity in which the person signs (if such capacity is not obvious from	reading the request		
wext to each signature, thatcate the name of the person sign	GEN!	HOA	reading the requesty.		
•	N. F. FE	(A)			
	图家車利	申祷刘名			
	A 國事	用章 20			
	All a				
	7				
	- For ree	Wing Office use only			
1. Date of actual receipt of the purported international application:  2 8 SEP 2005 (2 8 • 0 9 • 2 0 0 5)  2 Drawings:  received:					
3. Corrected date of actual receipt due to later but timely received papers or drawings completing the purported international application:					
4. Date of timely receipt of the required corrections under PCT Article 11(2):			not received:		
5. International Searching Authority (if two or more are competent): ISA /		6. Transmittal of search copy delayed until search fee is paid			
For International Bureau use only					
Date of receipt of the record copy by the International Bureau:					
			<u></u> j		



This sheet is not part of and does not count as a sheet of the international application.

### PCT

For receiving Office use only


 $\underbrace{\text{PCT/CN} \ 2005}_{\text{International Application No.}} \text{ / } 0 \ 0 \ 1 \ 5 \ \textbf{9} \ \textbf{4}$ FEE CALCULATION SHEET Annex to the Request 28 · SEP 2005 (2 8 · 0 9 · 2 0 0 5) Applicant's or agent's Date stamp of the receiving Office file reference FPEL05150044 Applicant INTEL CORPORATION etc. CALCULATION OF PRESCRIBED FEES **CNY500** T 1. TRANSMITTAL FEE . . . **CNY1500** S 2. SEARCH FEE . . . . International search to be carried out by (If two or more International Searching Authorities are competent to carry out the international search, indicate the name of the Authority which is chosen to carry out the international search.) 3. INTERNATIONAL FILING FEE Where items (b) and/or (c) of Box No. IX apply, enter Sub-total number of sheets Where items (b) and (c) of Box No. IX do not apply, enter Total number of sheets CHF1400 CHF1400 il first 30 sheets . . . . . number of sheets in excess of 30 fee per sheet i3 additional component (only if sequence listing and/or tables related thereto are filed in computer readable form under Section 801(a)(i), or both in that form and on paper, under Section 801(a)(ii)): CHF1400 CHE14:00 I Add amounts entered at i1, i2 and i3 and enter total at I . . . (Applicants from certain States are entitled to a reduction of 75% of the international filing fee. Where the applicant is (or all applicants are) so entitled, the total to be entered at I is 25% of the international filing fee.) P 4. FEE FOR PRIORITY DOCUMENT (if applicable) CNY2000CHF1 5. TOTAL FEES PAYABLE . . . . . . . . Add amounts entered at T, S, I and P, and enter total in the TOTAL box MODE OF PAYMENT authorization to charge deposit account (see below) coupons postal money order cash bank draft revenue stamps other (specify): cheque AUTHORIZATION TO CHARGE (OR CREDIT) DEPOSIT ACCOUNT Receiving Off (This mode of payment may not be available at all receiving Offices) Deposit Authorization to charge the total fees indicated above. Date: (This check-box may be marked only if the conditions for deposit accounts of the receiving Office so permit) Authorization to charge any deficiency or credit any overpayment in the total fees indicated above. Name:

Signature

Form PCT/RO/101 (Annex) (January 2004)

Authorization to charge the fee for priority document.

See Notes to the fee calculation sheet



20

# UPDATING ENTRIES CACHED BY A NETWORK PROCESSOR

#### **BACKGROUND**

[0001] A network communication system transmits information in packets from a transmitter to a receiver through one or more routers which route the packets between nodes within a network or between networks. The router may comprise one or more network processors to process and forward the packets to different destinations, and one or more external memories to store entries used by the network processors, such as node configuration data, packet queue and flow configuration data, etc.

[0002] The network processor may comprise a control plane to setup, configure and update the entries in the external memories, and a data plane having a plurality of microengines to process and forward the packets by utilizing the entries. Each of the microengines may have a local memory to store entries of the external memories that are frequently used. Once the control plane updates entries in the external memory, it may send a signal to the microengine(s) of the data plane that may cache or store the updated entries in its local memory. In response to the signal, the microengine(s) may flush all entries stored in the local memory to make them consistent with entries stored in the external memory.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0003] The invention described herein is illustrated by way of example and not by way of limitation in the accompanying figures. For simplicity and clarity of illustration, elements illustrated in the figures are not necessarily drawn to scale. For example, the dimensions of some elements may be exaggerated relative to

other elements for clarity. Further, where considered appropriate, reference labels have been repeated among the figures to indicate corresponding or analogous elements.

[0004] Fig. 1 shows an embodiment of a network device.

[0505] Fig. 2 shows an embodiment of a network processor of the network device of Fig. 1.

Fig. 3 shows an embodiment of a method implemented by a control plane [0006] of the network processor depicted in FIG. 2.

[0007] Fig. 4 shows an embodiment of another method implemented by a microengine of the network processor depicted in FIG. 2.

[8000] Fig. 5 shows a data flow diagram of an embodiment for updating entries cached by the network processor depicted in FIG. 2.

### **DETAILED DESCRIPTION**

[0009] The following description describes techniques for updating entries cached in a network processor. In the following description, numerous specific details 15 such as logic implementations, pseudo-code, means to specify operands, resource partitioning/sharing/duplication implementations, types and interrelationships of system components, and logic partitioning/integration choices are set forth in order to provide a more thorough understanding of the current invention. However, the invention may be practiced without such specific details. 20 In other instances, control structures, gate level circuits and full software instruction sequences have not been shown in detail in order not to obscure the invention. Those of ordinary skill in the art, with the included descriptions, will be able to implement appropriate functionality without undue experimentation.

[0010] References in the specification to "one embodiment", "an embodiment", "an example embodiment", etc., indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover,
5 such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to effect such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described.

[0011] Embodiments of the invention may be implemented in hardware, firmware, software, or any combination thereof. Embodiments of the invention may also be implemented as instructions stored on a machine-readable medium, that may be read and executed by one or more processors. A machine-readable medium may include any mechanism for storing or transmitting information in a form readable by a machine (e.g., a computing device). For example, a machine-readable medium may include read only memory (ROM); random access memory (RAM); magnetic disk storage media; optical storage media; flash memory devices; electrical, optical, acoustical or other forms of propagated signals (e.g., carrier waves, infrared signals, digital signals, etc.) and others.

[2012] An embodiment of a network device 8 to route packets of a network communication system is shown in Fig. 1. The network device 8 may comprise a network interface 10, a framer 11, one or more network processors 12/13, a switch fabric 14, and one or more external memories 15/16. Examples for the network device 8 may comprise an ATM switch (Asynchronous Transfer Mode),



an IP router (Internet Protocol), a SDH DXC (Synchronous Digital Hierarchy Datacross Connection), and the like.

[0013] The framer 11 may perform operations on frames. In an embodiment, the framer 11 may receive a line datagram from a network interface 10 of the network communication system, delimitate frames and extract payload, such as Ethernet packet from the frames. In another embodiment, the framer 11 may receive packets from network processor 13, encapsulate the packets into frames and map the frames onto the network interface 10. The framer 11 may further perform operations such as error detection and/or correction. Examples for the framer 11 may comprise a POS (packet over Synchronous Optic Network) framer, a High-Level Data Link (HDLC) framer or the like.

[0014] The network processors 12 and 13 may perform operations on packets. In an embodiment, the network processor 12 may process and forward the packets from the framer 11 to an appropriate port of another network device through the 15 switch fabric 14. For example, the network processor 12 may assemble IPv4 (Internet Protocol version 4) packets into CSIX (Common Switch Interface Specification) packets, modify packet headers and payloads, determine appropriate ports and forward the CSIX packets to the appropriate ports of the another network device. The network processor 13 may process and forward packets from the switch fabric 14 to appropriate ports 20 of the network interface 20 10 through the framer 11. For example, the network processor 13 may reassemble CSIX packets into IPv4 packets, modify packet headers and payloads, determine appropriate ports 20 and forward the IPv4 datagrams to the appropriate ports 20. Examples for the network processors 12 and 13 may comprise Intel® IXP 2XXX (e.g., IXP2400, IXP2800) network processors. 25



- [0015] The switch fabric 14 may receive and send packets from/to a network processor connected therewith. Examples for the switch fabric 14 may comprise a switch fabric conforming to CSIX or other fabric technologies such as HyperTransport, Infiniband, PCI-X, Packet-Over-Synchronous Optical Network, SapidIO, and Utopia.
- [0016] The external memories 15 and 16 may store entries 155/165 used by the network processors 12 and 13 to process and forward the packets. The entries may comprise node configuration data, queue configuration data, flow configuration data, network routing data, etc. The external memories 15 and 16
   10 may further buffer the packets. In one embodiment, the external memory 15/16 may comprise SDRAM (Synchronous Dynamic Random Access memory) to store packets and QDR SRAM (Quad Data Rate Static Random Access Memory) to store entries.
- [0017] Other embodiments may implement other modifications and variations on
  the structure of the network device as depicted in Fig. 1. For instance, the network
  processors 12 and 13 may perform framing duties instead of the framer 11 and
  the switch fabric may be omitted in a single-box scenario. For another instance,
  the network processors 12 and 13 may be integrated as one.
- [0018] An embodiment of the network processor 12 (or network processor 13) is shown in Fig. 2. As shown, the network processor 12 may comprise a control plane 211, a data plane 212 and a scratch pad 213 that are communicable with each other through a bus connection.
- [0019] The control plane 211 may be implemented as an integrated circuit (IC) with one or more processing cores 214<sub>1</sub> ... 214<sub>M</sub> such Intel® XScale® processing cores or StrongARM® processing cores to execute instructions to perform various



tasks. In an embodiment, the processing cores 214<sub>1</sub> ... 214<sub>M</sub> of the control plane 211 may execute instructions to setup, configure and update entries 155/165 stored in the external memories 15/16. For instance, the processing cores 214<sub>1</sub> ... 214<sub>M</sub> may update the external memories 15/16 which contain entries such as, for example, configuration data for nodes, configuration data for each packet queue, configuration data for each packet flow, etc. In another embodiment, the processing cores 214<sub>1</sub> ... 214<sub>M</sub> may further handle packets containing protocol message and routing information that may need relatively complex computations. For instance, the processing cores 214<sub>1</sub> ... 214<sub>M</sub> may process routing protocol packets containing routing information such as, for example, RIP (Routing Information Protocol) packets, OSPF (Open Shortest Path First) packets, and the like.

5

10

[0020] The data plane 212 may comprise a plurality of microengines 215<sub>1</sub> ... 215<sub>N</sub> in Fig. 2 that may be communicable with each other. Each of the microengines 15 may comprise a plurality of threads 2161 ... 216K to process and forward packets and one or more local memories 2181 ... 218N to store instruction code 220 and entries 224. The local memory 2181 ... 218N may comprise a control store, a memory, general purpose registers, transfer registers, and/or other storage mechanisms. In an embodiment, the local memories 2181 ... 218N may comprise 20 instruction code 220 executable by the threads 2161 ... 216K and one or more entries 224 consistent with the entries 155/165 of the external memories 15/16. The threads  $216_1 \dots 216_K$  may access the local memories  $218_1 \dots 218_N$  to fetch some useful information for packet forwarding. Entries 155/165 may be cached from the external memory 15/16 to the local memories 2181 ... 218N of the 25 microengines 215<sub>1</sub> ... 215<sub>N</sub> based upon some criteria, for example, whether the



entries 155/165 are frequently used by one or more microengines  $215_1 \dots 215_N$  of the data plane 212. Further, the entries 155/165 cached by one microengine  $215_1 \dots 215_N$  may be different from the entries 155/165 cached by another microengine  $215_1 \dots 215_N$ .

- [0521] The scratch pad 213 is accessible by both the processing cores 214<sub>1</sub> ... 214<sub>M</sub> of the control plane 211 and the microengines 215<sub>1</sub> ... 215<sub>N</sub> of the data plane 212. The scratch pad 213 may comprise a buffer 226<sub>1</sub> ... 226<sub>N</sub> to store data for each microengines 215<sub>1</sub> ... 215<sub>N</sub>. The buffers 226<sub>1</sub> ... 226<sub>N</sub> may be implemented using various structures such as, for example, ring buffers, link lists, stacks, etc. In other embodiments, the scratch pad 215 may be regarded as a flat memory.
- In an embodiment, processing cores 214<sub>1</sub> ... 214<sub>M</sub> of the control plane 211 may update one or more entries 155/165 in the external memories 15/16 by adding, deleting or changing one or more entries 155/165, and may write

  15 information related to the updated entries 155/165 to each buffer 226<sub>1</sub> ... 226<sub>N</sub> of the scratch pad 213 associated with a microengine 215<sub>1</sub> ... 251<sub>N</sub> that stores the updated entries 155/165 in its local memory 218<sub>1</sub> ... 218<sub>N</sub>. Then, the microengines 215<sub>1</sub> ... 215<sub>N</sub> may extract information from its buffer 226<sub>1</sub> ... 226<sub>N</sub>, read the updated entries 155/165 from the external memories 15/16 and update the

  20 corresponding entries 224 in the local memories 218<sub>1</sub> ... 218<sub>N</sub>. The information written in the buffers 226<sub>1</sub> ... 226<sub>N</sub> may comprise entry identifiers (e.g. addresses, entry numbers, entry pointers) that uniquely identify entries 155/165 of the external memories 15/16.
- [0023] Other embodiments may implement other modifications and variations on 25 the structure of the network processor as depicted in Fig. 2. For example, the



network processor 12 may further comprise a hash engine, a peripheral component interconnect (PCI) bus interface for communicating, etc.

[0024] Fig. 3 shows a process implemented by one or more processing cores 214<sub>1</sub> ... 214<sub>M</sub> of the control plane 211 to update an external entry 155/165 stored in an external memory 15/16. As shown, in block 301, the control plane 211 may update an entry 155 in the external memory 15. Then, in block 302, the control plane 211 may search for microengine(s) 215<sub>1</sub> ... 215<sub>N</sub> of the data plane 212 affected by the updated entry 155. In one embodiment, the control plane 211 determines a microengine 215<sub>1</sub> ... 215<sub>N</sub> is affected by the updated entry 155 by determining that the microengine 215<sub>1</sub> ... 215<sub>N</sub> has the updated entry 155 cached in its corresponding local memory 218<sub>1</sub> ... 218<sub>N</sub>.

The control plane 211 may implement block 302 in various ways. In an [0025] embodiment, the control plane 211 may determine the affected microengines 215<sub>1</sub>  $\dots$  215<sub>N</sub> by referring to a table of the external memory 15/16 or scratch pad 213 that lists the microengines  $215_1 \dots 215_N$  having cached a particular external entry 15 155. For example, the control plane 211 may supply a CAM (content addressable memory) of the external memory 15 with an identifier (e.g. an address, index, hash value, etc.) for the updated entry 155 to obtain a list of microengines 215 $_1\dots$  $215_{
m N}$  that have the entry 155 cached. In particular, the CAM may return a data word having at least N bits wherein each bit indicates whether a corresponding 20 microengine  $215_1 \dots 215_N$  has the updated entry 155 cached. However, it should be appreciated that the control plane 211 may utilize other techniques and structures to maintain a corresponds between entries 155/165 and the microengines  $215_1 \dots 215_N$  that have stored local copies of the entries 155/165.



- [0026] In block 303, the control plane 211 may write information associated with the external entry 155 updated in block 301 to buffers 226<sub>1</sub> ... 226<sub>N</sub> of microengines 215<sub>1</sub> ... 215<sub>N</sub> affected by the updated entry 155. The information may comprise identifiers that identify external entry 155/165 that have been updated by the control plane 211.
- [0027] For instance, if an entry 155 of external table 151 is updated in block 301, the control plane 211 may search for the microengines 215<sub>1</sub> ... 215<sub>N</sub>. that store the entry 155 in their local memories 218<sub>1</sub> ... 218<sub>N</sub> (block 302). Then, the control plane 211 in block 303 may write an identifier (e.g. address, entry number, entry pointer, and/or other data) for the updated entry 155 to the buffers 226<sub>1</sub> ... 226<sub>N</sub> of the affected microengines 215<sub>1</sub> ... 215<sub>N</sub> identified in block 302. For example, if the control plane 211 determines in block 302 that microengines 215<sub>1</sub> and 215<sub>N</sub> have cached the updated entry 155, then the control plane 211 in block 303 may write an identifier for the entry 155 to the corresponding buffers 226<sub>1</sub> and 226<sub>N</sub> to inform the microengines 215<sub>1</sub> and 215<sub>N</sub> that the identified entry 155 has been updated.
- [0028] In another embodiment, if all entries or more than a threshold level of entries of the external memory 15 are updated in block 301, the control plane 211 may forgo block 302 and write a wildcard identifier to the buffers 226<sub>1</sub> ... 226<sub>N</sub> indicating all cached entries 155 of the external memory 15 are invalid or outdated.
- [0029] Fig. 4 shows an embodiment of a method to update one ore more entries 224 of local memories 218<sub>1</sub> ... 218<sub>N</sub> of the data plane microengines 215<sub>1</sub> ... 215<sub>N</sub>. In block 402, one thread 216<sub>1</sub> ... 216<sub>K</sub> of each microengine 215<sub>1</sub> ... 215<sub>N</sub> of the data plane 212 may be designated or otherwise configured to perform the task of updating cached entries 224 of the microengine 215<sub>1</sub> ... 215<sub>N</sub>. In one



embodiment, the control plane 211 may designate a thread 216<sub>1</sub> ... 216<sub>K</sub> of each microengine 215<sub>1</sub> ... 215<sub>N</sub> that is to update the cached entries 224 of the microengine 215<sub>1</sub> ... 215<sub>N</sub>. Other embodiments may utilize other techniques to designate the thread to update the cached entries 224. For example, the microengine 215<sub>1</sub> ... 215<sub>N</sub> may designate the thread, the thread may be predetermined by the instruction code 220, and/or the thread designation may be hardwired into the microengine 215<sub>1</sub> ... 215<sub>N</sub>. In block 404, a thread 216<sub>1</sub> ... 216<sub>K</sub> of a microengine 215<sub>1</sub> ... 215<sub>N</sub> may be selected to continue executing its assigned tasks. To this end, the microengine 215<sub>1</sub> ... 215<sub>N</sub> and/or the control plane 211 may awaken and/or otherwise activate the selected thread using various thread scheduling algorithms such as, for example, round robin, priority, weighted priority, and/or other scheduling algorithms.

- [0030] In block 406, the selected thread 216<sub>1</sub> ... 216<sub>K</sub> may determine whether the selected thread 216<sub>1</sub> ... 216<sub>K</sub> is designated to update the local memory 218<sub>1</sub> ...
- 218<sub>N</sub> of its microengine 215<sub>1</sub> ... 215<sub>N</sub>. If selected thread 216<sub>1</sub> ... 216<sub>K</sub> determines in block 406 that another thread 216<sub>1</sub> ... 216<sub>K</sub> is designated for updates, then the selected thread 216<sub>1</sub> ... 216<sub>K</sub> in block 408 may continue to process packets in a normal fashion. If, however, the selected thread 216<sub>1</sub> ... 216<sub>K</sub> is designated to update its local memory 218<sub>1</sub> ... 218<sub>N</sub>, then the thread 216<sub>1</sub> ... 216<sub>K</sub> in block 410
- 20 may determine whether the buffer 226<sub>1</sub> ... 226<sub>K</sub> for its microengine 215<sub>1</sub> ... 215<sub>N</sub> indicates that entries 226 are invalid or outdated.
- [0031] The selected thread  $216_1 \dots 216_K$  may implement block 410 in various ways. For an embodiment wherein the buffers  $226_1 \dots 226_N$  are scratch rings, the selected thread  $216_1 \dots 216_K$  may execute a predetermined instruction (e.g.
- 25 'br\_!inp\_state[...]') of the instruction code 220 and may determine whether a



returned value of the predetermined instruction is true ('1') or false ('0'). The selected thread  $216_1\ldots 216_K$  may determine no updates are pending if the returned value is false, and likewise may determine one or more entries 226 of its local memory  $218_1\ldots 218_N$  are to be updated if the returned value is true.

- If the selected thread 216<sub>1</sub> ... 216<sub>K</sub> determines to update entries 224 of its local memory 218<sub>1</sub> ... 218<sub>N</sub>, the thread 216<sub>1</sub> ... 216<sub>K</sub> in block 412 may extract identifiers for the updated entries 155/165 from the buffer 226<sub>1</sub> ... 226<sub>N</sub> associated with the microengine 215<sub>1</sub> ... 215<sub>N</sub> of the thread 216<sub>1</sub> ... 216<sub>K</sub>. The information may comprise an entry identifier that uniquely identifies the updated entries
  10 155/165 of the external memories 15/16. Such an identifier may comprise an external memory number, an external memory pointer, an entry number, an entry pointer, and/or other identifying information from which an entry 155/165 may be discerned. However, if the selected thread 216<sub>1</sub> ... 216<sub>K</sub> determines to update no entries 224 of its local memory 218<sub>1</sub> ... 218<sub>N</sub>, the selected thread 216<sub>1</sub> ... 216<sub>K</sub>
  may continue to block 408 to perform normal packet processing.
- [0033] In block 414, the selected thread 216<sub>1</sub> ... 216<sub>K</sub> may read entries 155/165 from the external memory 15/16 that have been identified by information in its corresponding buffer 226<sub>1</sub> ... 226<sub>N</sub> as being updated. Further, the selected thread 216<sub>1</sub> ... 216<sub>K</sub> may update corresponding cached entries 224 based upon the entries read from the external memory 15/16 (block 416).
- [0034] Other embodiments may implement other modifications and variations to the process as depicted in Fig. 4. For example, a microengine 215<sub>1</sub> ... 215<sub>N</sub> may not assign a single thread 216<sub>1</sub> ... 216<sub>K</sub> to perform the task of updating local memory 218<sub>1</sub> ... 218<sub>N</sub>. Instead, each thread 216<sub>1</sub> ... 216<sub>K</sub> of the microengine 215<sub>1</sub>



 $\dots$  215<sub>N</sub> may determine whether to update entries 224 cached in its local memory 218<sub>1</sub>  $\dots$  218<sub>N</sub> before continuing with normal packet processing.

[0035] A data flow diagram illustrating an embodiment of updating entries 224 of local memories 218<sub>1</sub> ... 218<sub>N</sub> of the network processor 12 is shown in Fig. 5. As shown, the control plane 211 may update one or more external entries 155 in an external memory 15 (arrow 501). Then, the control plane 211 may write information associated with the updated external entries 155 to the buffers 226<sub>1</sub> ... 226<sub>N</sub> assigned to the affected microengines 215<sub>1</sub> ... 215<sub>N</sub> (arrow 502). In response to a thread 216<sub>1</sub> ... 216<sub>K</sub> determining, based upon information stored in its buffers 218<sub>1</sub> ... 218<sub>N</sub>, that one or more cached entries 224 of its microengine 215<sub>1</sub> ... 215<sub>N</sub> have been updated, the thread 216<sub>1</sub> ... 216<sub>K</sub> may read the updated external entries 155 from the external memory 15 (arrow 504) and update the corresponding local memory 218<sub>1</sub> ... 218<sub>N</sub> with the read entries 155 (arrow 505).

[0036] While certain features of the invention have been described with reference to example embodiments, the description is not intended to be construed in a limiting sense. Various modifications of the example embodiments, as well as other embodiments of the invention, which are apparent to persons skilled in the art to which the invention pertains are deemed to lie within the spirit and scope of the invention.

### What is claimed is:

1. A method of a network processor comprising a plurality of microengines that process network packets, the method comprising

updating an entry in a memory external to the network processor;

identifying a microengine of the plurality of microengines that has stored the entry in a local memory for the microengine; and

writing information to a buffer for the identified microengine that indicates the entry has been updated.

- 2. The method of claim 1 further comprising updating the entry in the local memory for the microengine in response to determining, based upon the information written to the buffer, that the entry has been updated.
  - 3. The method of claim 1 further comprising

reading the entry from the memory external to the network processor in response to determining, based upon the information written to the buffer, that the entry has been updated; and

updating the local memory for the microengine based upon the entry read from the memory external to the network processor.

4. The method of claim 1 further comprising

updating the entry in the local memory for the microengine in response to determining, based upon the information written to the buffer, that the entry has been updated; and

processing a network packet based upon the entry updated in the local memory for the microengine.

- 5. The method of claim 1 further comprising designating at least one
  thread of each microengine of the plurality of microengines to update entries of a corresponding local memory for each microengine based upon information stored in a corresponding buffer for each microengine.
- 6. The method of claim 1 further comprising activating a thread of the
   microengine to process information stored in the buffer and to update the local memory of the microengine based upon the information stored in the buffer.
  - 7. The method of claim 1 further comprising determining that all entries in the local memory for the microengine are invalid based upon the information stored in the buffer for the microengine.
  - 8. The method of claim 1 further comprising determining that all entries in the local memory for the microengine are outdated based upon the information stored in the buffer for the microengine.

20

15

9. A network processor to process network packets based upon entries stored in an external memory, comprising:



a plurality of microengines to process network packets, each microengine having a corresponding local memory to cache entries stored in the external memory and a corresponding buffer to identify entries in the local memory updated in the external memory, and

a control plane to update an entry in the external memory, to identify each microengine of the plurality of microengines having the entry stored in the corresponding local memory, and to store an identifier for the entry in the corresponding buffer for each identified microengine to indicate that the entry has been updated in the external memory.

10

5

10. The network processor of claim 9 wherein the control plane comprises at least one processing core to update the entry, to identify each microengine, and to store the identifier in the corresponding buffer for each identified microengine.

15

25

11. The network processor of claim 9 wherein each microengine reads the entry from the external memory in response to determining, based upon the identifier written to the corresponding buffer, that the entry has been updated, and

updates the corresponding local memory based upon the entry read from the external memory.

12. The network processor of claim 9 wherein each microengine updates the entry in the corresponding local memory in response to determining, based upon the identifier written to the corresponding buffer, that the entry has been updated, and



processes a network packet based upon the entry updated in the corresponding local memory.

- 13. The network processor of claim 9 wherein each microengine
  5 comprises a plurality of threads to process network packets and at least one
  thread to update entries of the corresponding local memory upon identifiers for
  entries stored in the corresponding buffer.
  - 14. A network device, comprising:
- a plurality of ports to transfer network packets;
  - a memory to store entries used to process network packets;
  - a network processor to process network packets based upon the entries stored in the memory external to the network processor, wherein the network processor comprises

a plurality of microengines to process network packets, each microengine having a corresponding local memory to cache entries stored in the external memory and a corresponding buffer to identify entries in the local memory updated in the external memory, and

at least one processing core to control the plurality of microengines, to update entries in the memory external to the network processor, to identify each microengine of the plurality of microengines having updated entries of the memory stored in corresponding local memory, and to store information in the corresponding buffer for each identified microengine to indicate updated entries of the memory.

25

15



15. The network device of claim 14 wherein each microengine reads updated entries from the memory based upon the information in the corresponding buffer, and

updates the corresponding local memory based upon the updated entries read from the memory.

- 16. The network device of claim 14 wherein each microengine updates entries in the corresponding local memory based upon information in their corresponding buffer, and
- processes network packets based upon the entries updated in the corresponding local memory.
  - 17. The network device of claim 14 wherein each microengine comprises a plurality of threads to process network packets, wherein at least one thread of the plurality of threads updates entries of the corresponding local memory based upon information in the corresponding buffer.
- 18. The network device of claim 14 wherein
  each microengine comprises a plurality of threads to process network
  packets, and

the at least one processing core designates at least one thread of each microengine to update entries of the corresponding local memory of the microengine based upon information in the corresponding buffer of the microengine.

25



19. A machine readable medium comprising a plurality of instructions that in response to being executed result in a network device

updating an entry in a memory external to a network processor of the network device;

identifying each microengine of the network processor that has cached the entry in a local memory of the network processor;

storing information to a corresponding buffer for each identified microengine, the information indicating the entry has been updated in the memory external to the network processor; and

updating the entry cached in the local memory based upon the information in the corresponding buffer for each identified microengine.

20. The machine readable medium of claim 19 wherein the plurality of instructions further result in the network device

reading the entry from the memory external to the network processor in response to determining, based upon the information written to the buffer, that the entry has been updated; and

updating the entry cached in the local memory based upon the entry read from the memory external to the network processor.

21. The machine readable medium of claim 19 wherein the plurality of instructions further result in the network device processing a network packet

based upon the updated entry cached in the local memory.

10




22. The machine readable medium of claim 19 wherein the plurality of instructions further result in the network device designating at least one thread of each microengine of the plurality of microengines to update entries of the local memory based upon information stored in the corresponding buffer for each microengine.



### **ABSTRACT**

Machine-readable media, methods, and apparatus are described to update entries cached in a network processor. In some embodiments, microengines of a network processor cache entries in corresponding local memories and update cached entries based upon information stored in corresponding buffers for the microengines. A control plane of the network processor identifies each microengine having updated entry stored in corresponding local memory, and store information in the corresponding buffer for each identified microengine to indicate that the entry has been updated in the external memory.










FIG. 2



3/5




FIG. 3



4/5





FIG. 4





)